

Our Products

by Sugano and Sons
Legendary Koetsu

ROSEWOOD STANDARD



BODY Natural Rosewood
TYPE Moving Coil
COIL WIRING Copper
MAGNET Samarium Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.4 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 8.9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz


ROSEWOOD SIGNATURE PLATINUM



BODY Rosewood w/Clear Laquer
TYPE Moving Coil
COIL WIRING Silverplated Copper
MAGNET Platinum Magnet
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.3 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

URUSHI VERMILLION



BODY Rosewood w/Urushi Laquer
TYPE Moving Coil
COIL WIRING Double Coil-Silverplated Copper
MAGNET Samarium-Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.2 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 2.5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

URUSHI TSUGARU



BODY Rosewood w/Urushi Laquer
TYPE Moving Coil
COIL WIRING Silverplated Copper
MAGNET Samarium-Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.4 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

URUSHI BLUE



BODY Rosewood w/Urushi Laquer
TYPE Moving Coil
COIL WIRING Silverplated Copper
MAGNET Samarium-Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.4 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

URUSHI WAGIMA



BODY Rosewood w/Urushi Laquer
TYPE Moving Coil
COIL WIRING Silverplated Copper
MAGNET Samarium-Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.4 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

URUSHI GOLD



BODY Rosewood w/Urushi Laquer
TYPE Moving Coil
COIL WIRING Silverplated Copper
MAGNET Samarium-Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.4 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 10 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

URUSHI BLACK



BODY Rosewood w/Urushi Laquer
TYPE Moving Coil
COIL WIRING Silverplated Copper
MAGNET Samarium-Cobalt
CANTILEVER Boron Cantilever
OUTPUT VOLTS 0.4 mV
FREQUENCY RANGE 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

KT International Ltd.
Hyogo, Japan

For inquiries contact us at
ktinter@nifty.com