

Ultimate quality

Koetsu cartridges, with their hand wound coils that transcend the boundaries between art and science, have long been the gold standard among cartridges.

CORALSTONE PLATINUM



BODY TYPE Coral Stone
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 12 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

JADE PLATINUM



BODY TYPE Jade
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 13 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

ONYX PLATINUM



BODY TYPE Onyx
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 12.5 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

BLOODSTONE PLATINUM



BODY TYPE Bloodstone
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 12.5 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

RHODONITE PLATINUM



BODY TYPE Rhodonite
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 13.5 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

TIGEREYE PLATINUM



BODY TYPE Tigereye
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 12.5 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

BLUE LACE ONYX PLATINUM



BODY TYPE Blue Onyx
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 12.5 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

AZULE PLATINUM



BODY TYPE Dumortierite
COIL WIRING Moving Coil
MAGNET Silverplated Copper
CANTILEVER Platinum Magnet
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.3 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 13 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

BLACK GOLDLINE



BODY TYPE Anodized Aluminum
COIL WIRING Moving Coil
MAGNET Copper
CANTILEVER Samarium Cobalt
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.4 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 10.8 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz

ROSEWOOD SIGNATURE



BODY TYPE Rosewood w/Clear Laquer
COIL WIRING Moving Coil
MAGNET Copper
CANTILEVER Samarium Cobalt
OUTPUT VOLTS Boron Cantilever
FREQUENCY RANGE 0.4 mV
 20Hz to 100kHz

CHANNEL SEPARATION 25db / 1kHz
INNER IMPEDANCE 5 Ohm
CHANNEL BALANCE .5 db / 1 kHz
RECOMMENDED IMPEDANCE 30 Ohm
WEIGHT 9 g
COMPLIANCE 5 X 10⁻⁶ cm/dyne at 100 hz